

DODPOPHM/USA/DOD/NADTR93011

PERFORMANCE ORIENTED PACKAGING TESTING OF CONTAINER, SHIPPING AND STORAGE, DL 1330411 FOR EIGHT IGNITERS FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

Author:

James M. Dwyer

Mechanical Engineering Technician

Performing Activity:
Naval Packaging, Handling, Storage and Transportation Center
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5023

October 1993

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Program Executive Office
Undersea Warfare (PMO 406)
Arlington, Virginia 22242-5769

93-26705

REPORT DCCUMENTATION PAGE

Form Approved OMB No 0704-0188

Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED			
	10/93	POP Test (09/93)			
4. TITLE AND SUBTITLE		5. FUNDING NUMBERS			
Performance Oriented Packaging Testing of Container, Shipping and Storage, DL 1330411, for Eight Igniters for Packing Group II Solid Hazardous Materials					
6. AUTHOR(S)					
James M. Dwyer					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER			
Naval Packaging, Handling, Stor and Transportation Center Naval Weapons Station Earle Colts Neck, NJ 07722-5023	age	DODPOPHM/USA/DOD/NADTR93011			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER			
Program Executive Office Undersea Warfare (PMO 406) 2531 Jefferson Davis Highway Arlington, VA 22242-5769		Same as above			
11. SUPPLEMENTARY NOTES					
N/A					
12a. DISTRIBUTION/AVAILABILITY STA	TEMENT	12b. DISTRIBUTION CODE			

13. ABSTRACT (Maximum 200 words)

This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Shipping and Storage Container (DL 1330411) for Eight Igniters meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 106 through 178, dated 1 October 1992. The packaged commodity used for the test was eight (8) simulated brass shapes weighing 0.9 kg (2.0 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 0.5 kg (1.1 pounds) were added. Gross weight of the loaded container was 3.0 kg (6.6 pounds). The test results indicate that the container has conformed to the POP requirements.

14. SUBJECT TERMS		15. NUMBER OF PAGES 7			
POP Test of Shipping and Storage Container (DL 1330411) for Eight Igniters		16. PRICE CODE			
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICA- TION OF THIS PAGE	19. SECURITY CLASSIFICA- TION OF ABSTRACT	20. LIMITATION OF ABSTRACT		
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL		

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Shipping and Storage Container (DL 1330411) for eight igniters meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 106 through 178, dated 1 October 1992. The packaged commodity used for the test was eight (8) simulated brass shapes weighing 0.9 kg (2.0 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 0.5 kg (1.1 pounds) were added. Gross weight of the loaded container was 3.0 kg (6.6 pounds).

Due to unavailability only one container was used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR 178.608. The container was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR 178.606. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 72 kg (158 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then removed and the container examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR 178.603. Six drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drops for each orientation):

- a. Horizontally.
- b. Diagonally on the edge between the cover assembly and the top ring of the container.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test


Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION DIFC QUELLING THE SCREED 5

-GCXXID 5 (



1. Base Level Vibration Test

The input vibration frequency was 4.2 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the container was inspected. The contents were completely retained by the container.

REFERENCE MATERIAL

- A. Code of Federal Regulations, Title 49 CFR, Parts 106-178.
- B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies) ATTN: DTIC/FDA Bldg. 5, Cameron Station Alexandria, VA 22304-6145

DLA Depot Operations Support Office Bldg. 32F, DGSE ATTN: Tom McElwee Richmond, VA 23297-5000

Commander Naval Surface Warfare Center ATTN: Crane Division (Code 4053) Crane, IN 47522-5000

TEST DATA SHEET

POP MARKING:

UN 1A2/3.0/S/**/USA/DOD/NAD

**YEAR LAST PACKED OR MANUFACTURED

Nomenclature: TBD

Type: 1A2 NSN: TBD

Drawing Number or P/N: Outer Packaging Material:

DL 1330411 Steel Drum

Dimension: Gross Weight:

5.71" dia x 5.19" H 3.0 kg (6.6 pounds)

Closure (Method/Type): Tare Weight:

Locking Ring, Nut, and Bolt 1.6 kg (3.5 pounds)

Additional Description:

PACKAGED COMMODITY:

Nomenclature: See table 1 NSN(s): See table 1

United Nations Number: See table 1

United Nations Packing Group: II

Physical State (Solid, Liquid, or Gas): Solid

Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A

Consistency/Viscosity: N/A | Density/Specific Gravity: N/A

Amount per Package: See table 1 Flash Point: N/A

Net Weight: See table 1

PACKAGED COMMODITY USED FOR TEST:

Name: Eight (8) Simulated Brass Shapes Physical State: Solid

Consistency: N/A Density/Specific Gravity: N/A

Test Pressure (Liquids Only): N/A | Net Weight: 1.4 kg (3.1 pounds)

Additional Description:

The net weight includes the current maximum commodity weight plus an additional 0.5 kg (1.1 pounds).

N/A = Not Applicable

TBD = To Be Determined

TABLE 1 Commodities Approved for Shipping in the Shipping and Storage Container (DL 1330411) for Eight Igniters

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Document Number	Haz Class/Div	UN Number	Units/ Package	Total Net Weight kg (lb)	Total Gross Weight kg (lb)
TBD	TBD	Igniter Assy DL 2526678	1330412	1.4G	0325	8	0.9 (2.0)	2.5 (5.5)

TBD = To Be Determined